



## ORI-30M

### Small Size 30 Watt Monocrystalline Solar Module

**Features**  
High power output module conversion efficiency with stable cell production technology.

Anti-reflective and anti-soiling surface reduces power loss from dirt and dust.

Outstanding performance in low-light irradiance environments.

Certified to withstand: wind load and snow load.

High salt mist and ammonia resistance certified by TUV Rheinland.

**Quality and Safety**  
Designed according to and complying with all requirements in IEC 61730 , IEC 61215, UL1703, CEC Listed, MCS and CE.

ISO 9001:2008:Quality management systems.  
ISO 14001:2004:Environmental management systems.  
BS OHSAS 18001:2007:Occupational health and safety management systems.



#### Applications

- On-grid residential roof-tops
- On-grid commercial/industrial roof-tops
- Solar power stations
- Other on-grid applications

## ORI-30M

#### Electrical Characteristics

Model	ORI-30M
Optimum Operating Voltage (Vmp)	18.57V
Optimum Operating Current (Imp)	1.62A
Open-Circuit Voltage (Voc)	22.64V
Short-Circuit Current (Isc)	1.73A
Cell Efficiency (%)	17.96%
Module Efficiency (%)	12.65%
Tolerance Wattage (e.g. +/-3%)	0 ~ +3%
Maximum Power(W)	30 Watt
NOCT	47°C +/- 2°C

#### General Characteristics

Solar Cell	156*30.6 (32.1) MONO
Number of Cells	2*18
Dimension	650mm*360mm*28mm
Weight	2.9KG
Front Glass	3.2mm tempered glass
Frame	28#
Allowable Hail Load	23m/s, 7.53 g
Classification	TPT backing, FF 70-76%,-40°C to +85°C

#### Temperature Coefficients

Temperature Coefficient of Im (%/°C)	+0.04
Temperature Coefficient of Pmax (%/°C)	-0.47
Temperature Coefficient of Voc (%/°C)	-0.38
Temperature Coefficient of Isc (%/°C)	+0.04
Temperature Coefficient of Vm (%/°C)	-0.38

#### Packing Solution

Packing	Wooden Box
Pieces per container	105pcs/Pallets

#### Engineering Drawing

